**Specification** SUZUKI GSXR 400RL-S and SP

GK76A-100001-

Overall Length: 1995 mm

Weight: 167 kg

Power: 59 ps @ 12.500 rpm

Engine Capacity: 398 cc

Bore and Stroke 56.0 x 40.4 mm

Valve clearances: 0.13 ~ 0.23 mm Inlet

Valve clearances: 0.20 ~ 0.30 mm Exhaust Gearbox oil capacity: 2900 cc approx Oil only

Gearbox oil capacity: 3200 cc Oil and filter Gearbox oil capacity: On rebuild

Fork oil capacity: 390 cc (sp 385 cc)
Fork oil air gap: 97 mm (sp 99 mm)

Fork oil type: 5wt

Tyre size front: 120/60/17
Tyre size rear: 160/60/17
Tyre pressure front: 29 psi

Tyre pressure rear: 32 ~ 36 psi

Chain size: 525v108

Chain slack: 25 ~ 35 mm
Battery type: YTX9BS
Spark plug type: CR8EK

Spark plug gap: 0.7 mm ~ 0.9 mm

Headlight bulb: 60/55 w 12 v

Main jet: 100# Pilot jet: 47.5#

Float height: 20, 4 mm

Mixture screw: 1.5 Turns out

Fuel tank capacity: 16 litre